T1S R4W DUCHESNE COUNTY MONUMENT SURVEY RECORD 1/4 FOUND 5/8" REBAR WITH PLASTIC CAP AT SEC 18+SEC 17 1/16 CORNER U.S.B.&M. P-5NAIL AND WASHER | IN FENCE CORNER ×).60' *FENCE* - x — x — x — x 17 32.81 1/4 CORNER 00.14,35" NORTH ₹ NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (1/16 CORNER) LOCATED AT LAT. 40°23'30.01130"N AND LONG. 110°23'18.53978"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' *30'* FOUND 5/8" REBAR AT 1/16 CORNER

DESCRIPTION OF CORNER EVIDENCE FOUND

POSITION OF CORNER DETERMINED BY SINGLE PROPORTIONATE MEASUREMENT

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET A 5/8" X 24" REBAR WITH 2½" ALUMINUM CAP AT POSITION OF 1/4 CORNER



PHOTO OF MONUMENT

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)

NAD83 UTAH CENTRAL ZONE
N: 7314733.629
E: 1955140.283

NAVD88 EL: 6893.61'

LATITUDE: 40°23'43.33763" N **LONGITUDE:** 110°22'12.02550" W

ELLIPSOID HEIGHT: 6841.86'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0040W0_200440



PHOTO CORNER FACING WEST

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date **29 JUN '18**

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

